

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1/ (currently amended): A method of monitoring ~~the~~ a proportion of a component in a gaseous mixture having at least two components and contained in an electrical switchgear enclosure, said method ~~consisting in~~ comprising:

measuring the pressure, the temperature, and the density of the gas mixture ~~by means of~~ using at least one sensor ~~sensors~~ mounted on said enclosure, and

~~in~~ determining said proportion by processing the measured values in a data-processing unit, so as to enable the mixture to be monitored non-intrusively.

2/ (original): A method according to claim 1, in which said proportion of a component in the mixture is calculated by the data-processing unit which is programmed to solve the thermodynamic state equations of said components.

3/ (original): A method according to claim 1, in which said proportion of a component in the mixture is determined by the data-processing unit which stores a data table in a memory, said data table containing a plurality of data items representative of various proportions of said component in correspondence with data items representative of various measurements of the pressure, of the temperature, and of the density of the gas mixture containing said component.

113
ant
4/ (original): A method according to claim 1, in which the density is measured by means of a vibrating-blade sensor.

5/ (original): A method according to claim 1, in which the density is measured by means of a capacitor whose capacitance is a function of the permittivity of the gas mixture.

6/ (original): A method according to claim 1, in which the density is measured by means of an interferometer.

7/ (original): A method according to claim 2, in which the data-processing unit is a microcomputer.

8/ (original): A method according to claim 2, in which the data-processing unit is formed by microprocessors or microcontrollers.

9/ (original): Electrical switchgear provided with an enclosure containing a mixture of at least two dielectric gases under pressure, wherein the proportions of the dielectric gases in the mixture are determined by implementing a method according to claim 1.

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. Application No. 10/038,585
Attorney Docket No. Q67992

10/ (original): Electrical switchgear according to claim 9, in which the gas mixture is made up of two components constituted by N₂ and SF₆ or by CF₄ and SF₆.

AS
Cont
11. (new): A method according to claim 1, further comprising running algorithms in the data-processing unit for correcting errors and drift specific to said at least one sensor.

12. (new): A system for monitoring a proportion of a component in a gaseous mixture having at least two components and contained in an electrical switchgear enclosure, comprising:

at least one sensor mounted on said enclosure for measuring the pressure, the temperature, and the density of the gas mixture; and

a data processing unit for processing the measured values, so as to enable the mixture to be monitored non-intrusively.

13. (new): A system for monitoring a proportion of a component in a gaseous mixture having at least two components and contained in an electrical switchgear enclosure, comprising:

first means mounted on said enclosure for measuring the pressure, the temperature, and the density of the gas mixture; and

second means for processing the measured values, so as to enable the mixture to be monitored non-intrusively.
